



## FT 7995


Avery Dennison FT 7995 is a double coated scrim tape with a dispersion-based modified acrylic adhesive used for bonding polyurethane foam, polyester fibers, felts and fabrics to a wide variety of substrates. Provides high adhesion to medium and low surface energy materials such as PP, PE, TPO, ABS, PVC, polystyrene and painted metals. Ideal for general purpose foam bonding applications such as gaskets, sound deadening and insulation materials in automotive, building and construction, appliance assembly and general industrial sub-assembly.

### FEATURES:

- Dispersion-based modified acrylic adhesive
- APEO free adhesive
- High initial tack
- Easy release glassine liner
- Broad range of service temperatures
- Polyester scrim reinforcement

### BENEFITS:

- Excellent resistance to solvents, chemicals, plasticizers, temperature and UV light
- Medium resistance to moisture
- Good conformability to flat or curved surfaces
- Immediate initial adhesion for part placement
- Excellent water jet and die cutting characteristics
- Helps provide tear resistance



### CONSTRUCTION:

#### Liner:

Havana (yellow/brown) glassine liner

#### Adhesive:

Dispersion-based modified acrylic

#### Carrier:

Polyester scrim

#### Adhesive:

Dispersion-based modified acrylic

## FT 7995

Adhesive Properties	Typical Values		
	US Mils	mm	Microns (µm)
THICKNESS			
Adhesive + Carrier	5.31	0.135	125+10
Liner	2.64	0.067	67
Total	7.95	0.202	202

\*PSTC-133

### PEEL ADHESION

2 mil PET; 180°; 12" / min

Substrate	Lbf / in	N / Meter
	72 hr	72 hr
Stainless steel	8.57	1500
ABS	7.99	1400
Polypropylene	7.42	1300

\*PSTC-101, ASTM D-3330, STD-10

### LOOP TACK

2 mil PET; 90°; 20" / min; 1" sq (6.5 cm<sup>2</sup>)

Substrate	Lbf / in	N / Meter
Stainless steel	5.71	1000
Finat tack	5.71	1000

\*PSTC-16, STD-7

### TEMPERATURES

Min. Application Temp.	50°F	10°C
Min. Service Temp.	-40°F	-40°C
Max. Service Temp.	310°F	155°C

\*TEST METHODS

Note: The listed values are typical only and not intended to serve as product specifications

## APPLICATION TECHNIQUES

- It is essential with all pressure-sensitive tapes the application surface is clean, dry and free of grease and oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (firm / rigid) surface achieves different performance

## STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 18-22°C / 64-72°F, 30-70% relative humidity and out of direct sunlight, in original packaging.

Please refer to [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com) for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2017 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance  
Tapes

**Asia Pacific**  
Kunshan, China,  
NO. 618 Nanhe Road  
Kunshan Economic &  
Technological Zone  
China, 215335  
Phone: +86 512 57155001  
Fax: +86 512 57155059

**Europe**  
Tieblokkenlaan 1  
B-2300 Turnhout  
Belgium  
Phone: +32 (0)14 40 48 11  
Fax: +32 (0)14 40 48 55

**Europe**  
Bld J.F. Kennedy 1  
7060 Soignies  
Belgium  
Phone: +32 (0)14 40 48 11  
Fax: +32 (0)14 40 48 55

**North America**  
250 Chester Street  
Painesville, Ohio  
44077 USA  
Phone: +1 866-462-8379  
Fax: +1 888-358-4469

For more information on our bonding tapes and adhesive solutions, visit [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com)