

FASSON® 1000S

HVAC Fastening Systems

Spray Adhesive

Not just tapes anymore!

FASSON® 1000S is a multi-purpose spray adhesive for most lightweight materials. It can be used in conjunction with FASSON® 0800 and 0810 foil tape products.

RECOMMENDATIONS

- Will cover 80 sq. feet per unit (17 fluid oz can) when applied as recommended*
- Apply 8" to 12" from nozzle to target surface

000s

· Nozzle is set to spray in a 4-6" pattern at this distance

FEATURES:

- High viscosity
- Excellent Tack
- Repositionable
- Designed to meet current government requirements



- · Consistent adhesive layer for optimum bonding
- · Fast, secure bond
- · Allows for flexible bond between irregular surfaces
- Specially formulated for bonding dissimilar substrates
 and other surfaces
- VOC compliant

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- · Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- · Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

· Store in a cool dry area away from heat and open flame

Please refer to Tapes. AveryDennison.com for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2015 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Asia Pacific Kunshan, China, NO. 618 Nanhe Road Kunshan Economic & Technological Zone China, 215335 Phone: +86 512 57155059 Europe Tieblokkenlaan 1 B-2300 Turnhout Belgium Phone: +32 (0)14 40 48 11 Fax: +32 (0)14 40 48 55 North America 250 Chester Street Painesville, Ohio 44077 USA Phone: +1 866-462-8379 Fax: +1 888-358-4469