



FASSON® 0950 BLACK


Avery Dennison[™] FASSON[®] 0950 Black is a 10 mil industrial grade cloth tape used for sealing joints and seams in HVAC applications.

FEATURES

- Rubber based adhesive
- Scrim reinforced facestock
- Available in silver and black

BENEFITS

- Strong bond to a variety of substrates
- Tri-directional FSK reinforces seal
- Tested in accordance with UL 723
- Made in the USA



CONSTRUCTION:

Facestock: Black Scrim Facestock Adhesive: Rubber



FASSON® 0950 BLACK				
Adhesive Properties:	Typical Values			
Thickness	ASTM D3652	US Mils	MM's	Micron's (µm)
Adhesive		2.1	0.05	53
Carrier		8.0	0.20	203
James		0.0	0.20	200
Fotal Caliper:		10.1	0.26	257
Peel Adhesion	ASTM D3330			
	@ Room Temp	L haf / im		N / Meter
Substrate	1-141-1	4.0		704
SS	Initial	4.0		704
	1	_1	l	
Static Shear	ASTM D3564			
180° 1" sq (6.5 cm2) 1000 g				
Substrate		Min to Fail		
SS	Initial	> 1440		
Tensile	ASTM D882			
	@ Break @ Room Temp			
Substrate		Lbf / in		N / Meter
Product	MD	27.0		4,755
				.,
			1	
	Elongation %	16.0		
TEMPERATURES		°F		°C
Minimum Application Temperature		40° F		4° C
Aaximum Continuous Operati	ng Temperature			
Maximum Intermittent Operating Temperature		200° F		95° C

THE LISTED VALUES ARE TYPICAL AND NOT INTENDED TO SERVE AS PRODUCT SPECIFICATIONS

APPLICATION TECHNIQUES

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil

Bond strength is dependent upon the amount of adhesive-to-surface contact developed ٠

Performance

Tapes

Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance •

STORAGE / SHELF LIFE

• One year when stored at 64-72°F (18-22°C) / 30-70% relative humidity, out of direct sunlight and in original packaging.

Please refer to Tapes.AveryDennison.com for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2020 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Asia Pacific Kunshan, China, NO. 618 Nanhe Road Kunshan Economic & Technological Zone China, 215335 Phone: +86 512 57155001 Fax: +86 512 57155059

Europe Tieblokkenlaan 1 B-2300 Turnhout Belgium Phone: +32 (0)14 40 48 11 Fax: +32 (0)14 40 48 55

North America 250 Chester Street Painesville, Ohio 44077 USA Phone: +1 866-462-8379 Fax: +1 888-358-4469