



## FASSON® 955


Designed to provide the surface of a foil tape and the easy application of a cloth tape for use on duct work.

**FEATURES:**

- Aggressive rubber based adhesive
- Metalized polycoated cloth

**BENEFITS:**

- Aggressive tack and adhesion
- Airtight, moisture-free seal
- Tested in accordance with UL 723

**CONSTRUCTION:****Carrier:**

Metalized Poly-coated Cloth

**Adhesive:**

Rubber

**FASSON® 955**

Adhesive Properties:		Typical Values		
Thickness	Test Method(s): PSTC-133	US Mils	MM's	Microns (µm)
Adhesive:		2.1	0.05	53
Carrier:		10.4	0.26	264
Total Caliper:		12.5	0.32	317

PEEL ADHESION		Test Method(s): PSTC-101, ASTM D-3330, STD-10		
Product 180° 12" min				
Substrate		Lbf / In	US Oz / In	N / Meter
SS	Initial	3.0	48	525

TENSILE		Test Method(s): PSTC-131, ASTM D-882, STD-3A,B,C		
Product				
Substrate		Lbf / In	US Oz / In	N / Meter
Product		1.6	26	280

ELONGATION		Test Method(s): PSTC-131, ASTM D-882, STD-3A,B,C		
Product				
Substrate		%		
Product		14.0		

STATIC SHEAR		Test Method(s): PSTC-107, ASTM D 3654, STD-9		
Product 1" sq (6.5 cm2) 2.2 lb (1.0 kg)				
Substrate		Min to Fail		
SS		> 15		

STATIC SHEAR		Test Method(s): PSTC-107, ASTM D 3654, STD-9		
Product 1" sq (6.5 cm2) 5.5 lb (2.5 kg)				
Substrate		Min to Fail		
SS	Initial	> 50		

TEMPERATURES		° F	° C
Min Application Temp			
Max Continuous Operating Temp			
Max Intermittent Operating Temp			

THE LISTED VALUES ARE TYPICAL AND NOT INTENDED TO SERVE AS PRODUCT SPECIFICATIONS

**APPLICATION TECHNIQUES**

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

**STORAGE / SHELF LIFE**

- One year when stored at 64-72°F (18-22°C) / 30-70% relative humidity, out of direct sunlight and in original packaging.

Please refer to [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com) for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2017 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance  
Tapes

Asia Pacific  
Kunshan, China,  
NO. 618 Nanhe Road  
Kunshan Economic &  
Technological Zone  
China, 215335  
Phone: +86 512 57155001  
Fax: +86 512 57155059

Europe  
Tieblokkenlaan 1  
B-2300 Turnhout  
Belgium  
Phone: +32 (0)14 40 48 11  
Fax: +32 (0)14 40 48 55

North America  
250 Chester Street  
Painesville, Ohio  
44077 USA  
Phone: +1 866-462-8379  
Fax: +1 888-358-4469