

250 Chester Street Painesville, Ohio 44077

866-GO-AVERY (866-462-8379) Phone:

Fax: 888-358-4469

email: psa.tape@averydennison.com

URL: tapes.averydennison.com **TEST REPORT**

PRODUCT: FT 8217

SUPPORT: NITRILE VINYL FOAM SUBSTRATE: **E-COATED METAL**

CERT NO .: 230103 - 0840

CHRYSLER MS-AY-522 B TYPE 1

OEM Rev Date: Jul 06

Polyvinyl / Nitrile (PVN) Blend Semi-Open Cellular Material

Cellular PVN with PSA

TEST PARAMETERS:

SECTION: 2.1 **Heat Aging** Shrink ASTM D3575-08*

> Specification: < 5% **Substrate** Results **Status** 2.1, Heat Aging, 30 mins @ 100° C **ABS** Stable, Less than 5% Length and Width **Pass**

> Specification: Substrate Results Status

> 2.1, Heat Aging, 30 mins @ 100° C Stable, Less than 5% Length and Width PP **Pass**

> Specification: < 5% **Substrate** Results Status **Pass**

2.1, Heat Aging, 30 mins @ 100° C Stable, Less than 5% Length and Width E-COATED METAL

SECTION: 2.2 Adhesion

Specification: No Adhesion Loss or Delamiantion

2.2, Adhesion, Cycles (2X) Substrate Results Status Good, Stable, no Lifting 72 hrs @ 70° C **ABS Pass**

24 hrs @ 38° C / 95% RH

72 hrs @ -40° C

Specification: **No Adhesion Loss or Delamiantion**

2.2, Adhesion, Cycles (2X) **Substrate** Results **Status** 72 hrs @ 70° C PP Good, Stable, no Lifting **Pass**

24 hrs @ 38° C / 95% RH

72 hrs @ -40° C

Specification: **No Adhesion Loss or Delamiantion**

2.2, Adhesion, Cycles (2X) **Substrate** Results Status Good, Stable, no Lifting 72 hrs @ 70° C E-COATED METAL **Pass**

24 hrs @ 38° C / 95% RH

72 hrs @ -40° C

CERTIFIED BY: ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

ANSI National Accreditation Board

ACCREDITED