



250 Chester Street
Painesville, Ohio 44077
Phone: **866-GO-AVERY (866-462-8379)**
Fax: **888-358-4469**
email: **psa.tape@averydennison.com**
URL: **tapes.averydennison.com**

TEST REPORT

PRODUCT: **FT 8302**
SUPPORT: **EPDM FOAM**
SUBSTRATE: **SS**
CERT NO.: **230103 - 0840**



CHRYSLER MS-AY-522 B TYPE 1
OEM Rev Date: Jul 06
Polyvinyl / Nitrile (PVN) Blend Semi-Open Cellular Material
Cellular PVN with PSA

TEST PARAMETERS:

SECTION: 2.1	Heat Aging	Shrink	ASTM D3575-08*		
Specification:	< 5%			Substrate	Results
2.1, Heat Aging, 30 mins @ 100° C				ABS	Stable, Less than 5% Length and Width
					Status
					Pass
Specification:	< 5%			Substrate	Results
2.1, Heat Aging, 30 mins @ 100° C				PP	Stable, Less than 5% Length and Width
					Status
					Pass
Specification:	< 5%			Substrate	Results
2.1, Heat Aging, 30 mins @ 100° C				E-COATED METAL	Stable, Less than 5% Length and Width
					Status
					Pass
Specification:	< 5%			Substrate	Results
2.1, Heat Aging, 30 mins @ 100° C				SS	Stable, Less than 5% Length and Width
					Status
					Pass
SECTION: 2.2	Adhesion				
Specification:	No Adhesion Loss or Delamination			Substrate	Results
2.2, Adhesion, Cycles (2X)				ABS	Good, Stable, no Lifting
72 hrs @ 70° C					Status
24 hrs @ 38° C / 95% RH					Pass
72 hrs @ -40° C					
Specification:	No Adhesion Loss or Delamination			Substrate	Results
2.2, Adhesion, Cycles (2X)				PP	Good, Stable, no Lifting
72 hrs @ 70° C					Status
24 hrs @ 38° C / 95% RH					Pass
72 hrs @ -40° C					
Specification:	No Adhesion Loss or Delamination			Substrate	Results
2.2, Adhesion, Cycles (2X)				E-COATED METAL	Good, Stable, no Lifting
72 hrs @ 70° C					Status
24 hrs @ 38° C / 95% RH					Pass
72 hrs @ -40° C					
Specification:	No Adhesion Loss or Delamination			Substrate	Results
2.2, , Cycles (2X)				SS	Good, Stable, no Lifting
72 hrs @ 70° C					Status
24 hrs @ 38° C / 95% RH					Pass
72 hrs @ -40° C					

CERTIFIED BY:

ISSUE DATE: **1-1-24**

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.