

250 Chester Street Painesville, Ohio 44077

866-GO-AVERY (866-462-8379) Phone:

Fax: 888-358-4469

email: psa.tape@averydennison.com

URL: tapes.averydennison.com **TEST REPORT**

PRODUCT: FT 8397

SUPPORT: NITRILE VINYL FOAM E-COATED-METAL SUBSTRATE: 230103 - 0841 CERT NO.:

ANSI National Accreditation Board

ACCREDITED

CHRYSLER MS-AY-522 B TYPE 1

OEM Rev Date: Jul 06

Polyvinyl / Nitrile (PVN) Blend Semi-Open Cellular Material

Cellular PVN with PSA

TEST PARAMETERS:

SECTION: 2.1 **Heat Aging** Shrink ASTM D3575-08*

Substrate Specification: Results < 5% **Status** Stable, Less than 5% Length and Width 2.1, Heat Aging, 30 mins @ 100° C **ABS Pass**

< 5% Specification: **Substrate** Results **Status**

Stable, Less than 5% Length and Width 2.1, Heat Aging, 30 mins @ 100° C PP **Pass**

Specification: < 5% **Substrate** Results **Status**

2.1, Heat Aging, 30 mins @ 100° C E-COATED-METAL Stable, Less than 5% Length and Width **Pass**

SECTION: 2.2 **Adhesion**

> Specification: No Adhesion Loss or Delamiantion 2.2, Adhesion, Cycles (2X) **Substrate** Results

Status 72 hrs @ 70° C **ABS** Good, Stable, no Lifting **Pass**

24 hrs @ 38° C / 95% RH

72 hrs @ -40° C

Specification: **No Adhesion Loss or Delamiantion**

2.2, Adhesion, Cycles (2X) **Substrate** Results Status Good, Stable, no Lifting 72 hrs @ 70° C **Pass**

24 hrs @ 38° C / 95% RH

72 hrs @ -40° C

Specification: No Adhesion Loss or Delamiantion

2.2, Adhesion, Cycles (2X) **Status Substrate** Results Good, Stable, no Lifting 72 hrs @ 70° C E-COATED-METAL **Pass**

24 hrs @ 38° C / 95% RH

72 hrs @ -40° C

CERTIFIED BY:

ISSUE DATE: 1-1-24

4-29-2003