



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 8392 12 PT BD
SUPPORT: PVC FOAM
SUBSTRATE: PP
CERT NO.: 230103 - 1010

FCA MS-AY-500-B -TYPE-3
CHRYSLER MS-AY-355 Apr 06
Cellular Polyvinyl Chloride (PVC)
B - Cellular Vinyl with Pressure Sensitive adhesive (PSA)

TAPE REQUIREMENTS:

Adhesive Requirements Table 2

Table with 5 columns: SECTION, Specification, Results, Status. Contains test results for Heat Aging, Odor, Adhesion, Burn Rate, etc.

CERTIFIED BY:

[Signature]

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.