



250 Chester Street
Painesville, Ohio 44077
Phone: **866-GO-AVERY (866-462-8379)**
Fax: **888-358-4469**
email: **psa.tape@averydennison.com**
URL: **tapes.averydennison.com**

TEST REPORT

PRODUCT: **FT 1126 12 PT BD**
SUPPORT: **0.5 MM SCRIM FELT**
SUBSTRATE: **PP**
CERT NO.: **230103 - 1038**

FCA MS-JZ-8-22
OEM Rev Date: Dec 16
Anti-Squeak Fabric, Pressure Sensitive



TAPE REQUIREMENTS:

SECTION: **Wear Resistance**

Taber Abrasion, Dry, 1000 Cycles, CS-10, 1000 g Load

Taber Abrasion, Wet, 1000 Cycles, CS-10, 500 g Load

ASTM D3884

Specification

No Noticeable Wear or Adhesive / Fiber Loosening

No Noticeable Wear or Adhesive / Fiber Loosening

Results

No Loosening of Fibers or Adhesive

No Loosening of Fibers or Adhesive

Status

Pass

Pass

SECTION: **Odor**

Dry, 1 hr @ 79°C

Wet, 1 hr @ 79°C - Deionized Water

ASTM J1351

Specification

No Disagreeable Odor

No Disagreeable Odor

Results

2 - Slight, But Noticeable Odor

2 - Slight, But Noticeable Odor

Status

Pass

Pass

SECTION: **Flammability**

Initial, Component

FMVSS 302

Specification

< 101.6 mm / min

Results

< B 25

Status

Pass

SECTION: **Tape Tests**

A. Original, 20 mins @ RT, Tape Tests,

B. 168 hours @ 110°C, Tape Tests,

C. Cycles (2X), Tape Tests, 16 hrs @ 38°C / 95% RH
24 hrs @ 110°C
6 hrs @ -29°C

D. Non-Condensing Humidity, 100 hrs @ 38°C / 95% RH, Tape Tests,

LP-463LB-19-01

Specification

No Adhesive Lifting

No Adhesive Lifting

No Adhesive Lifting

No Adhesive Lifting

Results

Good, Stable, No Lifting

Good, Stable, No Lifting

Good, Stable, No Lifting

Good, Stable, No Lifting

Status

Pass

Pass

Pass

Pass

SECTION: **Bond Peel Tests**

A. Original, 20 mins @ RT, Bond Peel Tests,

B. 168 hours @ 110°C, Bond Peel Tests,

C. Cycles (2X), Bond Peel Tests, 16 hrs @ 38°C / 95% RH
24 hrs @ 110°C
6 hrs @ -29°C

D. Non-Condensing Humidity, 100 hrs @ 38°C / 95% RH, Bond Peel Tests,

ASTM D1000

Specification

5.5 N / cm

4 N / cm

3.5 N / cm

3.5 N / cm

Results

8.8

5.9

6.9

11.2

Status

Pass

Pass

Pass

Pass

SECTION: **Resistance to Non-Condensing Humidity**

Resistance to Non-Condensing Humidity

LP-463KB-12-01

Specification

No fade, color changes or loosening of fibers

As Reported by Supplier

Results

Not Tested

Status

Not Tested

SECTION: **Resistance to Crocking Wet / Dry**

Resistance to Crocking Wet

Resistance to Crocking Dry

SAE J861

Specification

4 Min Rating

4 Min Rating

Results

Not Tested

Not Tested

Status

Not Tested

Not Tested

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.