



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: BNW 2028LV
SUPPORT: FELT
SUBSTRATE: ABS
CERT NO.: 230103 - 1041
FCA MS-JZ-8-22
OEM Rev Date: Dec 16
Anti-Squeak Fabric, Pressure Sensitive



TAPE REQUIREMENTS:

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Wear Resistance' tests for Taber Abrasion (Dry and Wet).

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Odor' tests for Dry and Wet conditions.

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Flammability' test for Initial Component.

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Tape Tests' (A, B, C, D) for Original, 168 hours, and various cycle conditions.

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Bond Peel Tests' (A, B, C, D) for Original, 168 hours, and various cycle conditions.

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Resistance to Non-Condensing Humidity' test.

Table with 5 columns: SECTION, Specification, Results, Status. Includes 'Resistance to Crocking Wet / Dry' tests.

CERTIFIED BY: [Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.