



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FBD 8393
SUPPORT: EPDM FOAM
SUBSTRATE: PP
CERT NO.: 230103 - 1224



FCA PF-10770
OEM Rev Date: Feb 15
Adhesion - PSA, Cellular and Fibrous Materials
Table 2 Flexible Composites

\*\* FCA 2015 Revision Requirements Are for Steel, Plastic Requirements to be Determined

TAPE REQUIREMENTS:

2.0 ENVIRONMENTAL REQUIREMENTS

SECTION: 2.1 Staining Resistance Determination

Table with 4 columns: Condition, Specification, Results, Status. Row 1: Vertical and Horizontal, 250 hrs @ 79°C; No Migratory Staining; No Evidence of Residue, Ghosting or Staining; Pass

SECTION: 2.2 Adhesive Heat Resistance Determination

Table with 4 columns: Condition, Specification, Results, Status. Multiple rows for different test conditions like LP-463TB-03-01\* and ASTM D1735, all showing 'No Adhesion Loss or Lifting' and 'Pass' status.

3.0 PHYSICAL, ELECTRICAL AND MECHANICAL REQUIREMENTS

SECTION: 3.0 Lap Shear

Table with 4 columns: Condition, Specification, Results, Status. Rows for Lap Shear tests at various temperatures and cycles, with results ranging from 32.4 to 41.5 N/cm and all 'Pass' status.

CERTIFIED BY:

Signature of Dave Nichols Jr.
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.