

 250 Chester Street

 Painesville, Ohio 44077

 Phone:
 866-GO-AVERY (866-462-8379)

 Fax:
 888-358-4469

 email:
 psa.tape@averydennison.com

 URL:
 tapes.averydennison.com

## **TEST REPORT**

PRODUCT: SUPPORT: SUBSTRATE: CERT NO.:

FCA PF.90175

OEM Rev Date: Mar 15

Pressure Sensitive Adhesives Includes Chrysler Standard PF-10770

Table 2 Flexible Composites

FT 1126 NITRILE VINYL FOAM IE: E-COATED METAL 230103 - 1101



TAPE REQUIREMENTS:			
SECTION: 3.0 Heat Resistance	<b>Specification</b>	<u>Results</u>	<u>Status</u>
2.2, Heat Resistance, Initial, 2 hrs @ RT	No Adhesion Loss or Lifting	Stable, No Lift or Adhesion Loss	Pass
SECTION: 3.0 Heat Resistance	Specification	Results	<u>Status</u>
2.2, Heat Resistance, 168 hrs @ 79°C	No Adhesion Loss or Lifting	Stable, No Lift or Adhesion Loss	Pass
			1 433
SECTION: 3.0 Heat Resistance	<b>Specification</b>	<u>Results</u>	<u>Status</u>
2.2, Heat Resistance, 8 hrs @ 93°C"	No Adhesion Loss or Lifting	Stable, No Lift or Adhesion Loss	Pass
SECTION: 3.0 Heat Resistance	Specification	<u>Results</u>	<u>Status</u>
2.2, Heat Resistance, 24 hrs Water Immersion	No Adhesion Loss or Lifting	Stable, No Lift or Adhesion Loss	Pass
SECTION: 3.0 Heat Resistance	Specification	Results	Status
2.2, Heat Resistance, Cycles (5x)	No Adhesion Loss or Lifting	Stable, No Lift or Adhesion Loss	Pass
72 hrs @ 70°C	-		
24 hrs @ 38°C / 95% RH			
24 hrs @ -29°C			
SECTION: 3.0 Peel Adhesion	Specification	Results	Status
3.0, Adhesion, Initial, 2 hrs @ RT	0.9 N / cm	7.0	Pass
SECTION: 3.0 Peel Adhesion 250 Chester Street	<b>Specification</b>	<u>Results</u>	<u>Status</u>
3.0, Adhesion, 168 hrs @ 79°C	3.3 N / cm	7.0	Pass
SECTION: 3.0 Peel Adhesion 250 Chester Street	Specification	Results	Ctatura
3.0, Adhesion, 8 hrs @ 93°C	3.3 N / cm	8.8	<u>Status</u> Pass
		0.0	1 455
SECTION: 3.0 Peel Adhesion	<b>Specification</b>	<u>Results</u>	<u>Status</u>
3.0, Adhesion, 24 hr Water Immersion	3.3 N / cm	8.8	Pass
		<b>-</b> <i>"</i>	<b>e</b>
SECTION: 3.0 Peel Adhesion	Specification	<u>Results</u>	<u>Status</u>

SECTION: **3.0 Peel Adhesion** 3.0, Adhesion, Heat Resistance, Cycles (5x) Adhesion, Heat Resistance, Cycles (5x) 72 hrs @ 70°C 24 hrs @ 38°C / 95% RH Specification 3.3 N / cm

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience. This laboratory is not accredited for the calibrations or tests marked \*.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

Original Test Date:

ISSUE DATE:

1-1-24

Pass

10.5

7-11-2017