TEST REPORT



250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 0900X SUPPORT: FLOCK SUBSTRATE: NONE

CERT NO.: 240208 - 0741



FMVSS 49 CFR 571 302 OEM Rev Date: Jun 22

Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS: SECTION: Flammability Initial, Component - Cabin Side	Specification < 102 mm / min		<u>Results</u> SE/NBR	Status Pass
Initial, Component - Cabin Side	< 102 mm/min		SE/NBR	Pass
Initial, Component - Cabin Side	< 102 mm/min		SE/NBR	Pass
Initial, Component - Cabin Side	< 102 mm / min		SE/NBR	Pass
Initial, Component - Cabin Side	< 102 mm / min		SE/NBR	Pass
CERTIFIED BY:		ISSUE DATE:	<u>1-1-24</u>	

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

Original Test Date: 2-8-2024

Page 1 of 1

David Nichols II, Automotive Lab Technician