



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: UHMW 527
SUPPORT: POLYETHYLENE
SUBSTRATE: FOIL
CERT NO.: 240131 - 0553

FMVSS 49 CFR 571 302
OEM Rev Date: Jun 22
Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS:

SECTION: Flammability
Initial, Component - Cabin Side

Specification
< 102 mm / min

Results
SE

Status
Pass

Initial, Component - Cabin Side

< 102 mm / min

SE

Pass

Initial, Component - Cabin Side

< 102 mm / min

SE

Pass

CERTIFIED BY:

[Signature]
David Nichols II, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.