



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1150
SUPPORT: 5 MIL UHMWPE
SUBSTRATE: POLYCARBONATE
CERT NO.: 240318 - 1159

FORD ESB M3G123-B
OEM Rev Date: Jan 20
Tape, Polyethylene, Pressure Sensitive, Interior (Antisqueak)

3.3 FILM PROPERTIES

Table with 4 columns: Section, Specification, Results, Status. Rows include Color, Thickness, Tensile Strength, Fogging, Adhesion, Resistance Properties, Heat Aging, Flammability, Odor, and Abrasion Resistance.

CERTIFIED BY: [Signature]
David Nichols II, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.