TEST REPORT



250 Chester Street Painesville, Ohio 44077

866-GO-AVERY (866-462-8379) Phone:

Fax: 888-358-4469

psa.tape@averydennison.com email: URL: tapes.averydennison.com

PRODUCT: FT 1143 SUPPORT: **PVC FOAM** SUBSTRATE: PP

CERT NO.: 221209 - 0842

FORD ESB-M3G76-B2

OEM Rev Date: Sep 05 Tape, PET - Two Sided PSA



TAPE REQUIREMENTS	APE REQUIRI	EMENTS:
-------------------	-------------	---------

SECTION 3.6.1 Peel Adhesion 3.6.1, Peel Adhesion, As Received, Initial RT	ASTM D3330	Specification 219 N/m	<u>Results</u> 305.3	Status Pass
SECTION 3.6.2 Aged 3.6.2, Aged, Aged, 72 hrs @ RT	ASTM D3330	Specification 657 N/m	<u>Results</u> 1210.7	Status Pass
SECTION 3.6.3 Aged, Cycles 3.6.3, Aged, Cycles, CycleTest (5x) 4 hrs @ 70° C 4 hrs @ 38° C / 95% RH 16 hrs @ -29° C 4 hrs @ 38° C / 95% RH 4 hrs @ 70° C 16 hrs @ -29° C	ASTM D3330	Specification 438 N/m	<u>Results</u> 1087.0	Status Pass

SECTION 3.7	Migration Stain	FLTM BO 115-1*	<u>Specification</u>	<u>Results</u>	<u>Status</u>
3.7, Migration Stain, 48 Hour Fluorescence, White Enamel		None	Not Applicable	NA	

SECTION 3.8	Liner Removal	ASTM D3330	Specification	Results	<u>Status</u>
3.8, Liner Remov	ral, Initial Release		55 N/m	23.9	Pass

SECTION 3.9 Storage Stability		<u>Specification</u>	<u>Results</u>	<u>Status</u>	
3.9, Storage Stab	ility, Liner Removal after 12 Months Below 32°C	No Appreciable Difference	Not Tested	TBD	

CERTIFIED BY:

Jake Cowdrick, Automotive Application Specialist

1-1-24 ISSUE DATE:

7-2-2002

Page 1 of 1

Original Test Date:

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.