

250 Chester Street Painesville, Ohio 44077

866-GO-AVERY (866-462-8379) Phone:

Fax: 888-358-4469

email: psa.tape@averydennison.com URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT 8392 SUPPORT: 2 MIL PET

SUBSTRATE: SS

230109 - 1042 CERT NO.:

FORD ESB-M3G76-B2

OEM Rev Date: Sep 05 Tape, PET - Two Sided PSA



Pass

TAPE REQUIREMENTS:

SECTION 3.6.1 **Peel Adhesion ASTM D1000 Specification Results Status**

3.6.1, Peel Adhesion, As Received, Initial RT 219 N/m 1229.4 **Pass**

SECTION 3.6.2 **Specification** Aged ASTM D1000 Results <u>Status</u>

1408.6 3.6.2, Aged, Aged, 72 hrs @ RT 657 N/m **Pass**

SECTION 3.6.3 Aged, Cycles **ASTM D1000** Specification Results **Status** 438 N/m 1523.0

3.6.3, Aged, Cycles, CycleTest (5x)

4 hrs @ 70° C

4 hrs @ 38° C / 95% RH

16 hrs @ -29° C

4 hrs @ 38° C / 95% RH

4 hrs @ 70° C

16 hrs @ -29° C

SECTION 3.7 **Migration Stain** FLTM BO 115-01* **Specification Results Status**

Not Applicable None 3.7, Migration Stain, 48 Hour Fluorescence, White Enamel NA

SECTION 3.8 **Liner Removal** ASTM D1000 **Specification** Results **Status**

25.1 3.8, Liner Removal, Initial Release 55 N/m **Pass**

Storage Stability **Specification** Results SECTION 3.9 **Status**

3.9, Storage Stability, Liner Removal after 12 Months Below 32°C No Appreciable Difference Not Tested **TBD**

CERTIFIED BY:

ISSUE DATE: 1-1-24

Dave Nichols Jr, Automotive Lab Technician

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience. This laboratory is not accredited for the calibrations or tests marked *.