



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FBR 8950 12 PT BD
SUPPORT: NITRILE VINYL FOAM
SUBSTRATE: PP
CERT NO.: 221209 - 0852



FORD ESB-M3G76-B2
OEM Rev Date: Sep 05
Tape, PET - Two Sided PSA

TAPE REQUIREMENTS:

#REF! #REF! #REF! #REF! Specification Results Status
#REF! #REF!

#REF! #REF! #REF! #REF! Specification Results Status
#REF! #REF! 657 N / m #REF! #REF!

SECTION 3.6.3 Aged, Cycles #REF! Specification Results Status
3.6.3, Aged, Cycles, CycleTest (5x) 438 N / m 939.8 Pass
4 hrs @ 70° C
4 hrs @ 38° C / 95% RH
16 hrs @ -29° C
4 hrs @ 38° C / 95% RH
4 hrs @ 70° C
16 hrs @ -29° C

SECTION 3.7 Migration Stain FLTM BO 115-1* Specification Results Status
3.7, Migration Stain, 48 Hour Fluorescence, White Enamel None Not Applicable NA

SECTION 3.8 Liner Removal ASTM D3330 Specification Results Status
3.8, Liner Removal, Initial Release 55 N / m 10.5 Pass

SECTION 3.9 Storage Stability Specification Results Status
3.9, Storage Stability, Liner Removal after 12 Months Below 32°C No Appreciable Difference Not Tested TBD

CERTIFIED BY: [Signature]
Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.