

250 Chester Street

Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT B 12 PT BD
SUPPORT: EPDM FOAM
SUBSTRATE: PAINTED METAL
CERT NO.: 221209 - 0841

FORD ESB-M3G76-B2

OEM Rev Date: Sep 05 Tape, PET - Two Sided PSA



TAPF	RFOL	JIRFN	IENTS:

SECTION 3.6.1 Peel Adhesion 3.6.1, Peel Adhesion, As Received, Initial RT	ASTM D3330	Specification 219 N/m	<u>Results</u> 840.0	Status Pass
SECTION 3.6.2 Aged 3.6.2, Aged, Aged, 72 hrs @ RT	ASTM D3330	Specification 657 N/m	<u>Results</u> 1507.3	<u>Status</u> Pass
SECTION 3.6.3 Aged, Cycles 3.6.3, Aged, Cycles, CycleTest (5x) 4 hrs @ 70° C 4 hrs @ 38° C / 95% RH 16 hrs @ -29° C 4 hrs @ 38° C / 95% RH 4 hrs @ 70° C 16 hrs @ -29° C	ASTM D3330	Specification 438 N/m	<u>Results</u> 1039.7	Status Pass

SECTION 3.7	Migration Stain	FLTM BO 115-1*	Specification	<u>Results</u>	<u>Status</u>
3.7, Migration Stain, 48 Hour Fluorescence, White Enamel		None	Not Applicable	NA	
SECTION 3.8	Liner Removal	ASTM D3330	Specification	Results	<u>Status</u>

SECTION 3.9 Storage Stability Specification Results Status

3.9, Storage Stability, Liner Removal after 12 Months Below 32°C

No Appreciable Difference

55 N/m

Not Tested TBD

Pass

CERTIFIED BY:

3.8, Liner Removal, Initial Release

Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: <u>1-1-24</u>

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

Original Test Date: 5-11-2005

Page 1 of 1

24.5