



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT A902 PET
SUPPORT: FLOCK
SUBSTRATE: ABS
CERT NO.: 240116 - 1104
FORD ESB M6G17-A
OEM Rev Date: Jul 12
Adhesion Requirements, PSA Antisqueak Flock

NOT FOR NEW DESIGN - NO REPLACEMENT

TAPE REQUIREMENTS:

Table with 5 columns: SECTION, Specification, SAE/ASTM/ISO, Results, Status. Contains 16 rows of test data for various tape properties like Fogging, Flock Fiber, Adhesive, Fabric, Pressure Sensitive Adhesive, Thickness, Loose Flock, Abrasion Resistance, Scuffing Resistance, Peel Adhesion, Shear Adhesion, RH Resistance, Heat Resistance, Odor, and Flammability.

CERTIFIED BY: [Signature]
David Nichols II, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.