

250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FBD 8970 12 PT BD

SUPPORT: PEU FOAM
SUBSTRATE: PAINTED METAL
CERT NO.: 221213 - 0756

FORD ESH-M11P40-A

OEM Rev Date: Sep 87 Adhesion Requirements

Pressure Sensitive Film with Biocide



3	Requirements
•	1 toquii oillollto

SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Status 0.22 N / mm 0.82 Pass

SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Status 3.2.2, Aged, Heat Aged, 7 days @ 88°C 0.22 N / mm 1.34 Pass

SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results O.96 Pass

SECTION 3.3 Peel Strength

3.3.1, Foam to Plastic Membrane, As Received

Specification
No Delamination

ASTM D3330
Results
Foam Tearing
Pass

SECTION 3.4 Bond Separation
Specification
Specification
Specification
ASTM D1000
Results
No Sip
Pass

SECTION 3.5 Quality Specification Results Status
3.5, Quality Removable Easily Removed Pass

SECTION 3.6 Bacteria / Fungus Resistance Specification Results
3.6, Bacteria / Fungus Resistance Must Pass Not Tested Pass

CERTIFIED BY: ISSUE DATE: 1-1-24

Dave Nichols Jr, Automotive Lab Technician

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

Original Test Date:

1-15-2012

Page 1 of 1