

250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com URL: tapes.averydennison.com

PRODUCT: **FBD 8970** SUPPORT: **PEU FOAM** SUBSTRATE: PAINTED METAL 221213 - 0756 CERT NO .:

TEST REPORT

FORD ESH-M11P40-A

OEM Rev Date: Sep 87 Adhesion Requirements

Pressure Sensitive Film with Biocide



TAPE REQUIREMENTS:

Requirements

SECTION 3.2 **Specification ASTM D3330** Peel Strength, Plastic Membrane to Panel **Results** Status 5 4 1 0.22 N/mm 1.09 **Pass**

3.2.1, As Received

SECTION 3.2 Peel Strength, Plastic Membrane to Panel **Specification ASTM D3330** Results **Status** 0.22 N/mm 1.76 **Pass**

3.2.2, Aged, Heat Aged, 7 days @ 88°C

SECTION 3.2 Peel Strength, Plastic Membrane to Panel

3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N/mm 1.11 **Pass**

Specification

Specification

Specification

ASTM D3330

ASTM D3330

ASTM D1000

Original Test Date:

1-15-2012

Page 1 of 1

Results

Results

Status

Status

SECTION 3,3 **Peel Strength**

Results Status 3.3.1, Foam Rubber to Plastic Membrane, As Received No Delamination Foam Tearing **Pass**

SECTION 3.4 **Bond Separation**

3.4, 200 gram load, 1 hr @ RT No Separation of Bond No Slip **Pass**

SECTION 3.5 Quality

Specification Results **Status** Easily Removed 3.5, Quality Readily Removable **Pass**

Bacteria / Fungus Resistance SECTION 3,6

Specification Results **Status** 3.6, Bacteria / Fungus Resistance **Must Pass** Not Tested **Pass**

CERTIFIED BY:

ISSUE DATE: 1-1-24

Dave Nichols Jr, Automotive Lab Technician

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.