## **TEST REPORT**



250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

888-358-4469 Fax:

email: psa.tape@averydennison.com

URL: tapes.averydennison.com PRODUCT: FT 8397

NITRILE VINYL FOAM SUPPORT: PAINTED METAL SUBSTRATE: 221213 - 0809 CERT NO.:

FORD WSB M3G212-A

OEM Rev Date: Feb 06

Tape, Low Density EPDM Foam, Pressure Sensitve, Supersoft



TADE	DEAL	IRFMF	NTC.
IAPE	ストいい	IRCIVICI	V 1.5

SECTION: <b>3.12</b> Pressure Sensitive Adhesion 3.12.1, Adhesion to Stainless Steel	ASTM D1000 Specification 500 N / m	<u><b>Results</b></u> 843.5	Status Pass
3.12.2, Adhesion to Painted Metal	500 N/m	594.9	Pass
SECTION 3.12 Adhesion to Stainless Steel 3.12.3, Adhesion, 30 mins @ 120°C, Inverted	Specification  No Adhesion Loss or Failure	Results Good, Stable, no lifting	Status Pass
3.12.3, Adhesion, Environmental Cycling 5x, Inverted 16 hrs @ 38°C / 95-100% RH 4 hrs @ -30C 4 hrs @ 90°C	No Adhesion Loss or Failure	Good, Stable, no lifting	Pass
SECTION: <b>3.14</b> Fogging 3.14, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT	SAE J1756 Specification 60 Units	<b>Results</b> 99.3	Status Pass
SECTION <b>3.15 Heat Shrink Resistance</b> 3.15, 21 days @ 121°C, Painted Metal - % Height Loss	Specification < 10% All Directions Height	Results 0%	Status Pass
3.15, 21 days @ 121°C, Painted Metal - % Height Loss	< 10% All Directions Width	3%	Pass
3.15, 21 days @ 121°C, Painted Metal - % Height Loss	< 10% All Directions Length	1%	Pass
SECTION: <b>3.16</b> Liner Removal 3.16, Liner Removal, Initial, Room Temp	ASTM D1000 <u>Specification</u> 2 - 11 N / m	Results 8.8	Status Pass

**CERTIFIED BY:** 

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

3-30-2007

Page 1 of 1

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.