



250 Chester Street  
 Painesville, Ohio 44077  
 Phone: **866-GO-AVERY (866-462-8379)**  
 Fax: **888-358-4469**  
 email: **psa.tape@averydennison.com**  
 URL: **tapes.averydennison.com**

**TEST REPORT**

PRODUCT: **FT 0900X PET**  
 SUPPORT: **FLOCK**  
 SUBSTRATE: **PP**  
 CERT NO.: **221213 - 0914**



**FORD WSS-M11P62-A**  
 OEM Rev Date: Jun 07  
 Performance Requirements for Adhesives Used in Interior Applications  
 Assembly Performance Parts Below the Belt Line

**TAPE REQUIREMENTS:**

SECTION:	Specification	Results	Status
<b>3.5 Odor</b> 3.5, 1 hr @ 65°C, Dry	SAE J1351* <b>2 Rating</b>	2 - Slight, But Noticeable Odor	<b>Pass</b>
3.5,1 hr @ 65°C, Wet	<b>2 Rating</b>	2 - Slight, But Noticeable Odor	<b>Pass</b>
<b>3.4 Flammability</b> 3.4, Flammability, Initial, Component	SAE J369 <b>100 mm / min</b>	<b>&lt; B25</b>	<b>Pass</b>
<b>3.6 Fogging</b> 3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT	SAE J1756 06 <b>70 Units</b>	96.1	<b>Pass</b>
3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT	<b>70 Units</b>	99.2	<b>Pass</b>

CERTIFIED BY:   
 Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.  
 This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.  
 Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.  
 This laboratory is not accredited for the calibrations or tests marked \*.

