



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1126 12 PT BD
SUPPORT: UHMWPE
SUBSTRATE: ABS
CERT NO.: 221213 - 0901



FORD WSS-M11P62-A
OEM Rev Date: Jul 05
Performance Requirements for Adhesives Used in Interior Applications
Assembly Performance Parts At or Above the Belt Line

TAPE REQUIREMENTS:

SECTION: 3.5 Odor SAE J1351* Specification 2 Rating Results Not Tested Status NT

SECTION: 3.4 Flammability SAE J369 Specification 100 mm / min Results B 17 Status Pass

SECTION: 3.6 Fogging SAE J1756 Specification 70 Units Results 93.1 Status Pass

3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT 70 Units 97.3 Pass

CERTIFIED BY:

Signature of Jake Cowdrick
Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.