



250 Chester Street
 Painesville, Ohio 44077
 Phone: 866-GO-AVERY (866-462-8379)
 Fax: 888-358-4469
 email: psa.tape@averydennison.com
 URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT 8217
 SUPPORT: 2 mm FELT
 SUBSTRATE: PAINTED METAL
 CERT NO.: 221213 - 0902



FORD WSS-M11P62-A
 OEM Rev Date: Jun 07
 Performance Requirements for Adhesives Used in Interior Applications
 Assembly Performance Parts Below the Belt Line

TAPE REQUIREMENTS:

SECTION:	SAE	Specification	Results	Status
3.5 Odor 3.15, 1 hr @ 65°C, Dry	SAE J1351*	2 Rating	2 - Slight, But Noticeable Odor	Pass
3.15, 1 hr @ 65°C, Wet		2 Rating	2 - Slight, But Noticeable Odor	Pass
3.4 Flammability 3.4, Flammability, Initial, Component	SAE J369	100 mm / min	EBRZT	Pass
3.6 Fogging 3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT	SAE J1756	70 Units	81.9	Pass
3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT		70 Units	100.0	Pass

CERTIFIED BY: 
 Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
 This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
 Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
 This laboratory is not accredited for the calibrations or tests marked *.