



250 Chester Street
Painesville, Ohio 44077
Phone: **866-GO-AVERY (866-462-8379)**
Fax: **888-358-4469**
email: **psa.tape@averydennison.com**
URL: **tapes.averydennison.com**

TEST REPORT


PRODUCT: **FT 8217**
SUPPORT: **3 mm FELT**
SUBSTRATE: **PAINTED METAL**
CERT NO.: **221213 - 0902**



FORD WSS-M11P62-A
OEM Rev Date: Jun 07
Performance Requirements for Adhesives Used in Interior Applications
Assembly Performance Parts Below the Belt Line

TAPE REQUIREMENTS:

SECTION:	SAE	Specification	Results	Status
3.5 Odor 3.15, 1 hr @ 65°C, Dry	SAE J1351*	2 Rating	2 - Slight, But Noticeable Odor	Pass
3.15, 1 hr @ 65°C, Wet		2 Rating	2 - Slight, But Noticeable Odor	Pass
3.4 Flammability 3.4, Flammability, Initial, Component	SAE J369	100 mm / min	EBRZT	Pass
3.6 Fogging 3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT	SAE J1756	70 Units	75.0	Pass
3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT		70 Units	98.4	Pass

CERTIFIED BY: 
Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.