

250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT 8270 SUPPORT: PEU FOAM

SUBSTRATE: PP

CERT NO.: 221213 - 0907

FORD WSS-M11P62-A OEM Rev Date: Jun 07

Performance Requirements for Adhesives Used in Interior Applications

ACCREDITED

TESTING LABORATORY

Assembly Performance Parts At or Above the Belt Line

TAPE REQUIREMENTS:

SECTION: 3.5 Odor SAE J1351* Specification Results Status
3.5, 1 hr @ 65°C, Dry 2 Rating 2 - Slight, But Noticeable Odor Pass

3.5,1 hr @ 65°C, Wet 2 Rating 2 - Slight, But Noticeable Odor Pass

SECTION: 3.4 Flammability SAE J369 Specification Results Status
3.4, Flammability, Initial, Component 100 mm / min SB50 Pass

SECTION: 3.6 Fogging SAE J1756 Specification Results Status 3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT 70 Units 100.0 Pass

3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT **70 Units** 100.0 **Pass**

Jake Cowdrick, Automotive Application Specialist

CERTIFIED BY:

ISSUE DATE: <u>1-1-24</u>

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077 Original Test Date: 1-20-2014 Page 1 of 1