



250 Chester Street  
 Painesville, Ohio 44077  
 Phone: 866-GO-AVERY (866-462-8379)  
 Fax: 888-358-4469  
 email: psa.tape@averydennison.com  
 URL: tapes.averydennison.com

**TEST REPORT**

PRODUCT: FT 8392  
 SUPPORT: PET FIBER  
 SUBSTRATE: PP  
 CERT NO.: 221213 - 0911



**FORD WSS-M11P62-A**  
 OEM Rev Date: Jun 07  
 Performance Requirements for Adhesives Used in Interior Applications  
 Assembly Performance Parts At or Above the Belt Line

**TAPE REQUIREMENTS:**


SECTION: <b>3.5</b> <b>Odor</b>	SAE J1351*	<u>Specification</u> <b>2 Rating</b>	<u>Results</u> 1 - No Noticeable Odor	<u>Status</u> <b>Pass</b>
3.5, 1 hr @ 65°C, Dry				

3.5,1 hr @ 65°C, Wet		<b>2 Rating</b>	1 - No Noticeable Odor	<b>Pass</b>
----------------------	--	-----------------	------------------------	-------------

SECTION: <b>3.4</b> <b>Flammability</b>	SAE J369	<u>Specification</u> <b>100 mm / min</b>	<u>Results</u> < B 25	<u>Status</u> <b>Pass</b>
3.4, Flammability, Initial, Component				

SECTION: <b>3.6</b> <b>Fogging</b>	SAE J1756	<u>Specification</u> <b>70 Units</b>	<u>Results</u> 103.1	<u>Status</u> <b>Pass</b>
3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT				

3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT		<b>70 Units</b>	100.5	<b>Pass</b>
---	--	-----------------	-------	-------------

CERTIFIED BY:   
 Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.