



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: psa.tape@averydennison.com  
URL: tapes.averydennison.com

**TEST REPORT**

PRODUCT: FT 8392  
SUPPORT: PEU FOAM  
SUBSTRATE: PP  
CERT NO.: 221213 - 0911



**FORD WSS-M11P62-A**  
OEM Rev Date: Jun 07  
Performance Requirements for Adhesives Used in Interior Applications  
Assembly Performance Parts At or Above the Belt Line

**TAPE REQUIREMENTS:**

SECTION: **3.5 Odor**  
3.5, 1 hr @ 65°C, Dry

SAE J1351\*

Specification  
**2 Rating**

Results  
2 - Slight, But Noticeable Odor

Status  
**Pass**

3.5,1 hr @ 65°C, Wet

**2 Rating**

2 - Slight, But Noticeable Odor

**Pass**

SECTION: **3.4 Flammability**  
3.4, Flammability, Initial, Component

SAE J369

Specification  
**100 mm / min**

Results  
< B 25

Status  
**Pass**

SECTION: **3.6 Fogging**  
3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT

SAE J1756

Specification  
**70 Units**

Results  
99.3

Status  
**Pass**

3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT

**70 Units**

99.7

**Pass**

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.