TEST REPORT



250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com

URL: tapes.averydennison.com

PRODUCT: FT 8306 SUPPORT: PE FOAM

SUBSTRATE: PP

CERT NO.: 221213 - 0820

FORD WSS M3G238 - A1 OEM Rev Date: Jan 10

Tape, Transit Film, Removable, Interior



TAPE REQUIREMENTS:

SECTION 3.6 Adhesion After Environmental Exposure - Interior (A1)*

<u>Specification</u> <u>Results</u> <u>Status</u>

3.6.1, Weathering Resistance, FLTM BO 116-01 0 No Adhesion Discoloration or Stain Not Tested NT

3.6.2, Heat Resistance, 7 days @ 90°C No Adhesion Discoloration or Stain Good, Removable, No Staining or Transfer Pass

3.6.3, Humidity Resistance, 7 days @ 38°C / 95-1(No Adhesion Discoloration or Stain Good, Removable, No Staining or Transfer Pass

3.6.4, Envornmental Cycle Resistance

5 hrs @ -30C

30 mins @ 23°C / 50% RH

5 hrs @ 90°C

30 mins @ 23°C / 50% RH

2 hrs @ 50°C / 95-100% RH

30 mins @ 23°C / 50% RH

5 hrs @ -30C

30 mins @ 23°C / 50% RH

5 hrs @ 90°C

No Adhesion Discoloration or Stain

Good, Removable, No Staining or Transfer

Pass

SECTION: **3.6.5 Odor*** 3.6.5, Odor, Dry - 1 hr @ 65°C

<u>Specification</u>

Results

Status

3 Max Rating

Clearly Perceptible, But Not Disturbing, 3

Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: <u>1-1-24</u>

9-12-2012

Page 1 of 1

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.