



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1115
SUPPORT: 2 MIL PET
SUBSTRATE: SS
CERT NO.: 230109 - 1047



GM 9985281
OEM Rev Date: Aug 03
Performance Requirements for Adhesive, Transfer Film
Table 1: Material Properties as Received
Table 2: Material Properties 90 Day Aged
Low Temperature

TAPE REQUIREMENTS:

Peel Adhesion

Table with 5 columns: SECTION, ASTM, Specification, Results, Status. Rows for Table 1 (Initial, 15 mins @ RT) and Table 2 (90 Day Aged @ 35°C, PET Support).

Table with 5 columns: SECTION, ASTM, Specification, Results, Status. Rows for Table 1 (High Temp, 1000g @ 23°C, PET Support) and Table 2 (90 Day Aged @ 35°C, 1000g @ 23°C, PET Support).

Passing high temperature requirements passes low temperature 25 minute holding power as well

Table with 5 columns: SECTION, ASTM, Specification, Results, Status. Rows for Table 1 (Initial, Room Temp) and Table 2 (90 Day Aged @ 35°C).

CERTIFIED BY: [Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.