



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: stus.averydennison.com

PRODUCT: FT 8217
SUPPORT: 2 MIL PET
SUBSTRATE: SS
STD CERT NO.: 230109 - 1049



GM 9985281
OEM Rev Date: Aug 03
Performance Requirements for Adhesive, Transfer Film
Table 1: Material Properties as Received
Table 2: Material Properties 90 Day Aged **
Low Temperature

TAPE REQUIREMENTS:

Peel Adhesion

Table with 5 columns: SECTION, ASTM, Specification, Results, Status. Rows include Table 1, Initial, 15 mins @ RT and Table 2, 90 Day Aged @ 35°C, PET Support.

Table with 5 columns: SECTION, ASTM, Specification, Results, Status. Rows include Table 1, Low Temp, 1000g @ 23°C, PET Support and Table 2, 90 Day Aged @ 35°C, PET Support.

Table with 5 columns: SECTION, ASTM, Specification, Results, Status. Rows include Table 1, Initial, Room Temp and Table 2, 90 Day Aged @ 35°C.

** Table 2 testing requires 90 day containerized aging @ 35C prior to test submission

CERTIFIED BY: [Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.