



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT A912
SUPPORT: FLOCK
SUBSTRATE: ABS
STD CERT NO.: 230913 - 0849

GMW 16875 TYPE IA-CYCLE-D
OEM Rev Date: Oct 18

Performance Requirements of Anti-Squeak, Itch, Rattle Fiber Tape
Type IA material is a flocked fabric or felt tape coated with a permanent acrylic PSA not exposed to UV
Initial

TAPE REQUIREMENTS:

Table with 5 columns: SECTION, ISO/ASTM, Specification, Results, Status. Rows include Liner Removal, Peel Adhesion, Shear Strength, Taber Abrasion, Flammability, Xenon Weatherometer, Odor, VOC, and Gravimetric Fogging.

CERTIFIED BY:

Signature of Dave Nichols Jr.
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.