



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1123
SUPPORT: 5 MIL UHMWPE
SUBSTRATE: ABS
CERT NO.: 221216 - 0950



GMW 16879 Type I Cycle M
OEM Rev Date: May 18
Performance Requirements of Ultra High Molecular Weight Polyethylene (UHMWPE) Tape
Type I material is UHMWPE film coated with a permanent acrylic PSA
Initial

TAPE REQUIREMENTS:

Table 1 Performance Requirements

Table with 5 columns: PROPERTIES, ISO, Specification, Results, Status. Rows include Liner Removal, Peel Adhesion, Dynamic Shear, Tensile Strength, Elongation, Fogging, and Flammability tests.

CERTIFIED BY: [Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.