



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: SA 1123
SUPPORT: 5 MIL UHMWPE
SUBSTRATE: ABS
STD CERT NO.: 241112 - 0927

GMW 16879 TYPE I CYCLE M
OEM Rev Date: May 18
Performance Requirements of Ultra High Molecular Weight Polyethylene (UHMWPE) Tape
Type I material is UHMWPE film coated with a permanent acrylic PSA
Initial

TAPE REQUIREMENTS:

Table 1 Performance Requirements

Table with 6 columns: PROPERTIES, Specification, Results, Mode, Status. Rows include Liner Removal, Peel Adhesion, Dynamic Shear, Tear Resistance, Tensile Strength, Elongation, Coefficient of Kinetic Friction, Fogging, and Flammability.

CERTIFIED BY: [Signature]
David Nichols II, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.