



250 Chester Street  
 Painesville, Ohio 44077  
 Phone: **866-GO-AVERY (866-462-8379)**  
 Fax: **888-358-4469**  
 email: **psa.tape@averydennison.com**  
 URL: **tapes.averydennison.com**

**TEST REPORT**

PRODUCT: **HPA 1905**  
 SUPPORT: **PRIMED EPDM**  
 SUBSTRATE: **SS**  
 CERT NO.: **221221 - 1257**



**HONDA 1752Z-SH3-0000**  
 OEM Rev Date: Aug 89  
 Tank Band Cushion

**TAPE REQUIREMENTS:**

SECTION: **6-1 Adhesion Properties**  
 6-1-3, Normal Condition

Specification  
**0.14 mPa (kg / cm2)**

Results  
 0.167

Status  
**Pass**

6-1-4, After Immersion, 24 hr @ 20°C, None

**0.14 mPa (kg / cm2)**

0.204

**Pass**

6-1-5, After Heat Aging, 70 hrs @ 100°C

**0.14 mPa (kg / cm2)**

0.347

**Pass**

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.