



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: HPA 9353
SUPPORT: PEU FOAM
SUBSTRATE: SS
CERT NO.: 221222 - 0735



TOYOTA TSK 6712G -1A- 30-N-LT
OEM Rev Date: Sep 05
Toyota Engineering Standard - Sealing Foams for Interior Trim

TAPE REQUIREMENTS:

Table with 5 columns: SECTION, FMVSS/ASTM, Specification, Results, Status. Rows include sections 6.2.1 (Flammability), 6.3 (Adhesive Peel Strength), 6.3 (Adhesive Shear Strength), 6.3 (Adhesive Durability, Peel Strength), and 6.3.7 (High Temp Bonding).

CERTIFIED BY:

Signature of Dave Nichols Jr.
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.