



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 7701
SUPPORT: FELT
SUBSTRATE: PAINTED METAL
CERT NO.: 221222 - 0736



TOYOTA TSM-0500G
OEM Rev Date: Nov 02
Flammability Test Method for Interior Non-Metallic Materials
Class C1
Composite Material
After Heat Aging

TAPE REQUIREMENTS:

2.2 Flammability

SECTION: 2.3.5 Flammability

2.3.5 (1) Original, Component

Table with 3 columns: Specification, Results, Status. Row 1: < 100 mm / min, DNI, Pass

2.3.5 (2) After 336 hr 70°C Heat Aging

Table with 3 columns: Specification, Results, Status. Row 1: < 100 mm / min, DNI, Pass

CERTIFIED BY:

Signature of Dave Nichols Jr.
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.