



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: stus.averydennison.com

PRODUCT: FT 1149X
SUPPORT: EPDM RUBBER
SUBSTRATE: PP
STD CERT NO.: 221222 - 0740



TOYOTA TSM 1712G -1
OEM Rev Date: Feb 07
Materials for Fuel Tank Cushion
Low Water Absorption, Heat Resistant Rubbers

TEST PARAMETERS:

SECTION: 4.1 Adhesion Strength Test ASTM D3330

Table with 4 columns: Specification, Results, Status. Row 1: 49.0 kPa, 82.3, Pass. Row 2: 4.11, Adhesion Strength Test, 48 hrs @ RT, 82.3, Pass.

TOYOTA TSM 1712G - 3
OEM Rev Date: Feb 07
Materials for Fuel Tank Cushion
Similar To Class 1 Rubbers But Has Lower Tensile Strength And Greater Hardness

TEST PARAMETERS:

SECTION: 4.1 Adhesion Strength Test ASTM D3330

Table with 4 columns: Specification, Results, Status. Row 1: 49.0 kPa, 82.3, Pass. Row 2: 4.11, Adhesion Strength Test, 48 hrs @ RT, 82.3, Pass.

CERTIFIED BY:

Handwritten signature of Dave Nichols Jr.

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.