



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FBA 8960
SUPPORT: 5 MM XLPE FOAM
SUBSTRATES: ALUMINUM
CERT NO.: 221222 - 0743

VALEO PDT NVC 00001-C
Rev Date: Apr 11
Plastic Foam Seals - Material Specification

TEST PARAMETERS:

Table with 5 columns: SECTION, FMVSS/GMW/ISO, Specification, Results, Status. Rows include Flammability, Odor, Fogging, Mildew, Aging Test 3 (Initial, 48 hrs, Thermal Shock), and Aging Test 3 (Initial, 48 hrs, Thermal Shock).

CERTIFIED BY:

Signature of Dave Nichols Jr.
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.