



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT A902
SUPPORT: FLOCK
SUBSTRATE: FOIL
CERT NO.: 231114 - 1143



VOLKSWAGEN AG PV 3015
Test Method Rev Date: May 94
Non-Metallic Materials for Interior Trim

PV 50180

TAPE REQUIREMENTS:

SECTION: Fogging, Oil Bath

PV 3015*

Sample 1, 16 hrs @ 100°C, 21°C Cooling, Post - 4 hrs @ RT (desiccator)

Specification

2 mg

Results

1.4000

Status

Pass

Sample 2, 16 hrs @ 100°C, 21°C Cooling, Post - 4 hrs @ RT (desiccator)

Specification

2 mg

1.6000

Pass

Sample 3, 16 hrs @ 100°C, 21°C Cooling, Post - 4 hrs @ RT (desiccator)

Specification

2 mg

1.2000

Pass

CERTIFIED BY:

Handwritten signature of David Nichols II

David Nichols II, Automotive Lab Technician

ISSUE DATE:

1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.