



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FL 1008
SUPPORT: FOIL
SUBSTRATE: 20% TALC FILLED PP
CERT NO.: 230915 - 0809

VOLVO VCS 5031,19
OEM Rev Date: Aug 04
Flammability of Interior Materials

TAPE REQUIREMENTS:

S4 Requirements

Table with 5 columns: SECTION, FMVSS 302, Specification, Results, Status. Rows include tests for Initial, Component - Machine Direction, 60 sec and 14 Days @ 70°C / 95% RH.

CERTIFIED BY:

Signature of Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.