

TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: Fasson 0808
SUPPORT: FOIL
SUBSTRATE: ABS
CERT NO.: 230901 - 0827


VOLVO VCS 5031,19
OEM Rev Date: Aug 04
Flammability of Interior Materials

TAPE REQUIREMENTS:

S4 Requirements

SECTION: Flammability	FMVSS 302	<u>Specification</u>	<u>Results</u>	<u>Status</u>
Initial, Component - Machine Direction, 60 sec		< 80 mm / min	DNI	Pass
Initial, Component - Cross Direction, 60 sec		< 80 mm / min	DNI	Pass
SECTION: Flammability		<u>Specification</u>	<u>Results</u>	<u>Status</u>
14 Days @ 70°C, Component - Machine Direction, 60 sec		< 80 mm / min	DNI	Pass
14 Days @ 70°C, Component - Cross Direction, 60 sec		< 80 mm / min	DNI	Pass
SECTION: Flammability		<u>Specification</u>	<u>Results</u>	<u>Status</u>
14 Days @ 38°C / 95% RH, Component - Machine Direction		< 80 mm / min	DNI	Pass
14 Days @ 38°C / 95% RH, Component - Cross Direction, 60 sec		< 80 mm / min	DNI	Pass

CERTIFIED BY:



ISSUE DATE: 1-1-24

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.