TEST REPORT



250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: URL: tapes.averydennison.com

psa.tape@averydennison.com

FT 0900X

SUPPORT: **FLOCK** PP SUBSTRATE:

PRODUCT:

CERT NO.: 240201 - 1441

VOLVO VCS 5031,19

OEM Rev Date: Aug 04

Flammability of Interior Materials



TAPE REQUIREMENTS:

S4 Requirements

SECTION: Flammability Initial, Component - Machine Direction, 60 sec	FMVSS 302 Specification < 80 mm / min	Results SE/NBR	Status Pass
Initial, Component - Cross Direction, 60 sec	< 80 mm / min	SE/NBR	Pass
SECTION: Flammability 14 Days @ 70°C, Component - Machine Direction	Specification n, 60 sec < 80 mm / min	Results <b25< th=""><th>Status Pass</th></b25<>	Status Pass
14 Days @ 70°C, Component - Cross Direction, 6	60 sec < 80 mm / min	<b25< td=""><td>Pass</td></b25<>	Pass
SECTION: Flammability 14 Days @ 38°C / 95% RH, Component - Machin	Specification e Direction < 80 mm / min	Results <b25< td=""><td>Status Pass</td></b25<>	Status Pass
14 Days @ 38°C / 95% RH, Component - Cross I	Direction, 6 < 80 mm / min	<b25< td=""><td>Pass</td></b25<>	Pass

CERTIFIED BY:

David Nichols II, Automotive Lab Technician

1-1-24

ISSUE DATE:

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077 Original Test Date: 1-31-2024 Page 1 of 1