



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1123
SUPPORT: EVA FOAM
SUBSTRATE: PP
CERT NO.: 230103 - 0830



CHRYSLER MS-AY-518-B1
OEM Rev Date: Oct 10
Ethylene Vinyl Acetate (EVA) - Cellular - Water and Dust Seals

TAPE REQUIREMENTS:

Table 2 Physical Properties of Adhesive Systems

Table with 5 columns: TEST, Specification, Results, Status. Contains 4 rows of test data including Initial, Extended Term Heat Aging, Thermo Cycling, and Burn Rate tests.

CERTIFIED BY: [Signature]

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

Original Test Date: 5-25-2004 Page 1 of 1