



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 8397
SUPPORT: SHODDY PAD
SUBSTRATE: ABS
CERT NO.: 230103 - 0831



CHRYSLER MS-AY-518-B2
OEM Rev Date: Oct 10
Ethylene Vinyl Acetate (EVA) - Cellular - Water and Dust Seals

TAPE REQUIREMENTS:

Table 2 Physical Properties of Adhesive Systems

Table with 5 columns: TEST, Specification, Results, Status. Contains 8 test entries including Initial, Extended Term Heat Aging, Thermo Cycling, Short Term Heat Aging, and Burn Rate.

CERTIFIED BY: [Signature]

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.