



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1115
SUPPORT: PORON FOAM
SUBSTRATE: PP
CERT NO.: 230103 - 0948

CHRYSLER MS-CC-235
OEM Rev Date: Oct 04
Adhesion - PSA, Low Density Foam Sealing Applications
B - Supported Adhesive for Die Cut Parts

TEST PARAMETERS:

Table with 4 columns: SECTION, Specification, Reference, Results, Status. Contains 4 rows of test data for Adhesion section 2.2.

Cycles (3x)
72 hrs @ 70°C
24 hrs @ 38° C / 95% RH
72 hrs @ -40°C

Table with 4 columns: SECTION, Specification, Reference, Results, Status. Contains 4 rows of test data for Adhesion section 3.0.

Cycles (3x)
72 hrs @ 70°C
24 hrs @ 38° C / 95% RH
72 hrs @ -40°C

CERTIFIED BY:

Handwritten signature of Dave Nichols Jr.

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

Original Test Date: 8-1-2007 Page 1 of 1