



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: A904 2PT
SUPPORT: WHITE FLOCK
SUBSTRATE: ABS
CERT NO.: 230103 - 1031
FCA MS-JZ-8-22
OEM Rev Date: Dec 16
Anti-Squeak Fabric, Pressure Sensitive



TAPE REQUIREMENTS:

Table with 5 columns: SECTION, Specification, Results, Status. Rows include: Wear Resistance (ASTM D3884), Odor (ASTM J1351), Flammability (FMVSS 302), Tape Tests (LP-463LB-19-01), Bond Peel Tests (ASTM D1000), Resistance to Non-Condensing Humidity (LP-463KB-12-01), Resistance to Crocking Wet / Dry (SAE J861).

CERTIFIED BY: [Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.