

250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

psa.tape@averydennison.com email: URL:

tapes.averydennison.com

TEST REPORT

PRODUCT: FT 0900X **FLOCK** SUPPORT: SUBSTRATE: **ABS**

CERT NO.: 230103 - 1059

FCA PF.90175

OEM Rev Date: Mar 15 Pressure Sensitive Adhesives Includes Chrysler Standard PF-10770

Table 2 Flexible Composites



Status

Pass

Status

Pass

Status

Pass

TAPE REQUIREMENTS:

SECTION: 3.0 **Heat Resistance** 2.2, Heat Resistance, Initial, 2 hrs @ RT

SECTION: 3.0 **Heat Resistance** 2.2, Heat Resistance, 168 hrs @ 79°C

Heat Resistance SECTION: 3.0 2.2, Heat Resistance, 8 hrs @ 93°C"

SECTION: 3.0 **Heat Resistance** 2.2, Heat Resistance, 24 hrs Water Immersion

SECTION: 3.0 **Heat Resistance** 2.2, Heat Resistance, Cycles (5x) 72 hrs @ 70°C

3.0, Adhesion, Initial, 2 hrs @ RT

3.0, Adhesion, 168 hrs @ 79°C

3.0, Adhesion, 8 hrs @ 93°C

3.0, Adhesion, 24 hr Water Immersion

3.0, Adhesion, Heat Resistance, Cycles (5x)

24 hrs @ 38°C / 95% RH 24 hrs @ -29°C

Peel Adhesion

Peel Adhesion

Peel Adhesion

Peel Adhesion

Peel Adhesion

Specification

No Adhesion Loss or Lifting

Specification No Adhesion Loss or Lifting

Specification No Adhesion Loss or Lifting

Specification No Adhesion Loss or Lifting

Specification No Adhesion Loss or Lifting

Results

Stable, No Lift or Adhesion Loss

Results Stable, No Lift or Adhesion Loss

Results

Stable, No Lift or Adhesion Loss

Results Status Stable, No Lift or Adhesion Loss **Pass**

Results **Status** Stable, No Lift or Adhesion Loss **Pass**

Specification Results **Status** 0.9 N/cm 13.7 **Pass**

Specification Results **Status** 3.3 N/cm 15.2 **Pass**

Specification Results Status 3.3 N/cm 15.7 **Pass**

Specification Results Status 3.3 N/cm 6.9 **Pass**

Specification Results Status

15.3 3.3 N/cm **Pass**

24 hrs @ 38°C / 95% RH

72 hrs @ 70°C

CERTIFIED BY:

SECTION: 3.0

SECTION: 3.0

SECTION: 3.0

SECTION: 3.0

SECTION: 3.0

Dave Nichols Jr, Automotive Lab Technician

Adhesion, Heat Resistance, Cycles (5x)

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.